



Lantern Hanger Adjustable Clamp

Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: HENG TONG
- Model Number: PB-150A
- Minimum Order Quantity: 1000 pieces
- Price: \$0.50 - \$5.00/pieces
- Packaging Details: CARTON+PALLET, or as per your requirement.
- Supply Ability: 1000000 Piece/Pieces per Month



Product Specification

- Material: Metal
- Standard Or Nonstandard: Standard
- Usage: Pipe Clamp
- Structure: Wave Clamp
- Size Range: 1/2" To 10"
- Port: Shanghai
- Highlight: Adjustable Clamp Lantern Hanger, Adjustable Lantern Hanger



More Images



Product Description

Lantern Hanger Adjustable Clamp

They come in different sizes and configurations to accommodate various pipe diameters and types.

Pipe clamps have a versatile design that allows for easy installation and adjustment.

These clamps are commonly used in plumbing, construction, and industrial projects for pipe support and alignment.

Adjustable Clamp

Size Range: 1/2" (15mm) to 10" (30mm)



PB型吊夹配用吊头

Red Head for PB-Type Lantern Hanger



吊头编号 Part No.	材料尺寸 (mm) Size of Steel	设计荷载 (KN) Design Load
M10	1.5*25	2.9
M12	2.5*32	5.4
M16	3.0*50	12.7

卡夹编号 Part No.	公称直径 (In) Pipe Size	管材外径 (mm) O.D. Size	材料尺寸 (mm) Size of Steel	吊杆 Rod	螺栓 Bolt	设计荷载 (KN) Design Load	
						铰链式 Hinge	叉式 Cross
PB-015A		19.1	1.6*25	M10	M6*25	1.2	2.3
PB-015	1/2	21.7	1.6*25	M10	M6*25	1.2	2.3
PB-020A		25.0	1.6*25	M10	M6*25	1.2	2.3
PB-020	3/4	27.2	1.6*25	M10	M6*25	1.2	2.3
PB-025	1	34.0	1.6*25	M10	M6*25	1.2	2.3
PB-032	1 1/4	42.7	1.6*25	M10	M6*25	1.2	2.3
PB-040	1 1/2	48.6	1.6*25	M10	M6*25	1.2	2.3
PB-050	2	60.5	1.6*25	M10	M6*25	1.2	2.3
PB-065	2 1/2	76.3	2.3*2.5	M10	M8*25	1.5	3.1
PB-080	3	89.1	2.3*2.5	M10	M8*25	1.5	3.1
PB-100A		110.0	2.3*2.5	M10	M8*25	1.5	3.1
PB-100	4	114.3	2.3*2.5	M10	M8*25	1.5	3.1
PB-125	5	139.8	3.0*32	M12	M10*40	2.1	3.9
PB-150A		159.0	3.0*32	M12	M10*40	2.1	3.9
PB-150	6	165.2	3.0*32	M12	M10*40	2.1	3.9
PB-200	8	216.3	3.0*38	M16	M12*50	2.5	4.7
PB-C-250	10	267.4	4.0*38	M16	M12*50	3.3	6.2

52

Material: Steel

Function: Recommended for the suspension of non-insulated pipe or insulated pipe with a shield.

Note: When an oversized clevis is used, a pipe spacer should be placed over the cross bolt to assure that the lower U-strap will not move in on the bolt. When attaching seismic bracing to the clevis hangers, a bolt (cross bolt spacer) must be installed. See Seismic Restraints Approval Guidelines.

Maximum Temperature: 650°F (343°C).

Standard Finish: Plain, Electro-Galvanized, or Hot-Dip Galvanized

also available in Stainless Steel

Order By: Part number and finish.

Feature :

- 1) Bigger adjusting range
- 2) Evenly stress when fastening
- 3) Wrest resistant and high crushing strength
- 6) sizes: by customers' requirements
- 7) high quality and competitive price
- 8) It has different bandwidths as per the different sizes.

9)The band thickness is also different for different bandwidths





package



shipment



FAQ

Q: Are you trading company or manufacturer ?

A: We are factory.

Q: How long is your delivery time?

A: Generally it is 5-10 days if the goods are in stock. or it is 15-30 days if the goods are not in stock, it is according to quantity.

Q: Do you provide samples ? is it free or extra ?

A: Yes, we could offer the sample for free charge but do not pay the cost of freight.

Q: What is your terms of payment ?

A: Payment<=3000USD, 100% in advance. Payment>=3000USD, 30% T/T in advance ,balance before shippment.
If you have another question, pls feel free to contact us as below:



Wuxi Hengtong Metal Framing System Co., Ltd.



+86 15251535252



elinglu@htstrut.com



channel-fittings.com

No 6 East Dingxiang Road Hudai Industry Zone Wuxi City 214161 China